

c2 3. (Amended) The driving circuit of the display device according to claim 1, wherein said active device has a first transistor, a drain of which is connected to said resistor, a source of which supply power is applied to and a gate voltage of which is controlled by said controlling means, and a second transistor a drain of which is connected to said resistor, a source of which is connected to a ground and a gate voltage of which is controlled by said controlling means.

c3 6 7. (Amended) The driving circuit of the display device according to claim 1, wherein a voltage outputted from said gray shade voltage generating means is a positive polarity voltage and a negative polarity voltage.

7 8. (Amended) The driving circuit of the display device according to claim 1, wherein, when bits of said digital image data are N, said high order bits are composed of (N-1) bits counted from the most significant bit of said digital image data and the low order bit is composed of one bit counted from the least significant bit of the digital image data.

**Please enter the following amended claims:**

c4  
cmt 8 14. (New) A driving circuit of a display device for displaying a plurality of gray shades based on inputted digital image data comprising:

a gray shade voltage generating circuit for generating a plurality of voltages;

a gray shade voltage selecting circuit for selecting one voltage out of a plurality of voltages supplied from said gray shade voltage generating circuit based on high order bits

composed of at least one bit counted from the most significant bit of said digital image data, and  
for outputting said voltage;

an operational amplifier used to amplify a voltage outputted from said gray shade voltage  
selecting circuit; and

a voltage adjusting circuit for inducing a voltage rise or a voltage drop of a voltage  
outputted from said operational amplifier based on low order bits of said digital image data,

wherein said voltage adjusting circuit is comprised of a resistor, one end of which is  
connected to an output terminal of said operational amplifier, an active device connected to  
another end of said resistor and controlling circuit for controlling operations of said active device  
based on said low order bits of said digital image data, wherein said other end of said resistor is  
connected to said display device.

C4  
cont

9 ~~15.~~ (New) The driving circuit of the display device according to claim ~~14~~<sup>8</sup>, wherein  
said active device has a first transistor, a drain of which is connected to said another end of said  
resistor, a source of which supply power is applied to and a gate voltage of which is controlled  
by said controlling circuit, and a second transistor a drain of which is connected to said another  
end of said resistor, a source of which is connected to a ground and a gate voltage of which is  
controlled by said controlling circuit.

10 ~~16.~~ (New) The driving circuit of the display device according to claim ~~14~~<sup>8</sup>, wherein  
said resistor is composed of an analog switch.

Preliminary Amendment  
Application Number 09/505,192

Atty Docket Number Q57919

11 ~~17~~. (New) The driving circuit of the display device according to claim ~~14~~, wherein a voltage outputted from said gray shade voltage generating circuit is a positive polarity voltage and a negative polarity voltage.

C4  
Cmcd 12 ~~18~~. (New) The driving circuit of the display device according to claim 1, wherein, when bits of said digital image data are N, said high order bits are composed of (N-1) bits counted from the most significant bit of said digital image data and the low order bit is composed of one bit counted from the least significant bit of the digital image data.--

---